



BRW-3000A Infant Radiant Warmer


- Skin temp. and manual control by micro-computer
- Over temperature alarm
- Available adjustment of radiator and mattress tilting
- With one illumination light
- APGAR timer
- RS-232 connector

BRW-3000B Infant Radiant Warmer

- Based on BRW-3000A. added with
- Phototherapy



Phototherapy unit(option)



Low-pressure suction



Radiation head that can be adjusted in horizontal angulation



Free-step mattress tilting adjust



X-ray tray(option)

Specifications Infant Incubator

Model	BRW-3000A	BRW-3000B
Electrical requirement	~ 220V 50Hz or ~ 230V 60Hz	
Power consumption	≤ 700VA	
Air mode temp. range	25.0℃ ~ 37.0℃	
Over temp. alarm	< 38.0℃	
High mode temp. range	37.1℃ ~ 38.0℃	
High mode temp. alarm	< 39.0℃	
Temp. deviation alarm	± 1.0℃	
Skin sensor accuracy	≤ ± 0.3℃	
Mattress temp. uniformity	≤ 2.0℃	
Heating rate	≤ 30min	
APGAR timing	1min、5min、10min	

Model	BRW-3000A	BRW-3000B
screen	LED	
skin temperature sensor	●	●
suction	option	
O ₂ bottle	option	
phototherapy	option	●